



TL-R1200C-RP

Drive Bay	12 x 3.5-inch SATA 6Gb/s, 3Gb/s
Drive Compatibility	3.5-inch SATA hard disk drives 2.5-inch SATA hard disk drives 2.5-inch SATA solid state drives
Audio Alert On/Off Switch	Yes
Form Factor	2U Rackmount
Host Interface	1 x USB 3.2 Gen 2 Type-C
LED Indicators	HDD 1-12, Status, Link, Fan error
Buttons	Power switch
Dimensions (HxWxD)	88.6 × 482 × 562.5 mm
Weight (Net)	11.03 kg
Weight (Gross)	14.29 kg
Max. number of HDDs/SSDs supported	12
Hard Drive Type	3.5-inch SATA hard disk drives 2.5-inch SATA hard disk drives 2.5-inch SATA solid state drives
Operating temperature	0 - 40 °C (32°F - 104°F)
Relative Humidity	5-95% RH non-condensing, wet bulb: 27°C (80.6°F)
Power Supply Unit	250W PSU, 100 - 240V
Power Consumption: Operating Mode, Typical	82.26 W
Fan Mode Switch	Yes (Auto, high, medium, low)
Fan	2 x 70mm, 12VDC
Sound Level	33.4 db(A)
System Warning	Buzzer

Note: Use only QNAP memory modules to maintain system performance and stability. For NAS devices with more than one memory

note. Use only QNAP memory modules to maintain system performance and stability. For NAS devices with more than one memory slot, use QNAP modules with identical specifications. Warning: Using unsupported modules may degrade performance, cause errors, or prevent the operating system from starting.

* Sound Level Test Environment: Refer to ISO 7779; Maximum HDD loaded; Bystander Position; Average data from 1 meter in front of operating NAS.

Designs and specifications are subject to change without notice.