



TL-R400S	
Drive Bay	4 x 3.5-inch SATA 6Gb/s, 3Gb/s
Drive Compatibility	3.5-inch SATA hard disk drives 2.5-inch SATA hard disk drives 2.5-inch SATA solid state drives
Audio Alert On/Off Switch	Yes
Form Factor	1U Rackmount
Host Interface	1 x SFF-8088
LED Indicators	HDD 1-4, Status, Link, Fan error
Buttons	Power switch
Dimensions (HxWxD)	43.9 × 438.9 × 291.1 mm
Weight (Net)	3.98 kg
Weight (Gross)	5.38 kg
Max. number of HDDs/SSDs supported	4
Hard Drive Type	
Tidia Dilive Type	3.5-inch SATA hard disk drives2.5-inch SATA solid state drives
Operating temperature	2.5-inch SATA hard disk drives
	2.5-inch SATA hard disk drives 2.5-inch SATA solid state drives
Operating temperature	2.5-inch SATA hard disk drives 2.5-inch SATA solid state drives 0 - 40 °C (32°F - 104°F)
Operating temperature Relative Humidity	2.5-inch SATA hard disk drives 2.5-inch SATA solid state drives 0 - 40 °C (32°F - 104°F) 5-95% RH non-condensing, wet bulb: 27°C (80.6°F)
Operating temperature Relative Humidity Power Supply Unit Power Consumption:	2.5-inch SATA hard disk drives 2.5-inch SATA solid state drives 0 - 40 °C (32°F - 104°F) 5-95% RH non-condensing, wet bulb: 27°C (80.6°F) 100W PSU, 100 - 240V
Operating temperature Relative Humidity Power Supply Unit Power Consumption: Operating Mode, Typical	2.5-inch SATA hard disk drives 2.5-inch SATA solid state drives 0 - 40 °C (32°F - 104°F) 5-95% RH non-condensing, wet bulb: 27°C (80.6°F) 100W PSU, 100 - 240V 25.07 W
Operating temperature Relative Humidity Power Supply Unit Power Consumption: Operating Mode, Typical Fan Mode Switch	2.5-inch SATA hard disk drives 2.5-inch SATA solid state drives 0 - 40 °C (32°F - 104°F) 5-95% RH non-condensing, wet bulb: 27°C (80.6°F) 100W PSU, 100 - 240V 25.07 W Yes (Auto, high, medium, low)
Operating temperature Relative Humidity Power Supply Unit Power Consumption: Operating Mode, Typical Fan Mode Switch Fan	2.5-inch SATA hard disk drives 2.5-inch SATA solid state drives 0 - 40 °C (32°F - 104°F) 5-95% RH non-condensing, wet bulb: 27°C (80.6°F) 100W PSU, 100 - 240V 25.07 W Yes (Auto, high, medium, low) 2 x 40mm, 12VDC

Kensington Security Slot Yes

Note: Use only QNAP memory modules to maintain system performance and stability. For NAS devices with more than one memory slot, use QNAP modules with identical specifications. Warning: Using unsupported modules may degrade performance, cause errors, or prevent the operating system from starting.

* Sound Level Test Environment: Refer to ISO 7779; Maximum HDD loaded; Bystander Position; Average data from 1 meter in front of operating NAS.

Designs and specifications are subject to change without notice.