



## QSW-308-1C

Management Type	Unmanaged
Number of Ports	11
10GbE SFP+	2
10GbE SFP+/RJ45 Combo Ports	1
1GbE (RJ45)	8
Power Supply Description	Adapter
Max. Power Consumption	36W
Input Power Type	AC
Input Voltage Range	100-240VAC, 50/60 Hz
MAC Address Table	16K
Total Non-Blocking Throughput	38Gbps
Switching Capacity	76Gbps
Fan	Fanless
Fanless	Yes
Supported Standards	IEEE 802.3 Ethernet IEEE 802.3u 100BASE-TX IEEE 802.3ab 1000BASE-T IEEE 802.3an 10GBASE-T IEEE 802.3bz 2.5G/5G BASE-T Multi-Gig Ethernet
Form Factor	Desktop
LED Indicators	Per Port: Speed/Link/Activity Per System: Power/Status
Dimensions (HxWxD)	42.5 × 290 × 127 mm
Weight (Net)	0.77 kg
Weight (Gross)	1.19 kg

Operating Temperature	0 - 40°C / 32~104°F
Relative Humidity	5~95% Non-condensing
Certifications	CE, FCC, VCCI, BSMI RCM, CCC
Electromagnetic Compliance	CLASS B, UL62368
Jumbo Frames	10k
Warranty	2 Years

Note: Use only QNAP memory modules to maintain system performance and stability. For NAS devices with more than one memory slot, use QNAP modules with identical specifications.

Warning: Using unsupported modules may degrade performance, cause errors, or prevent the operating system from starting.

\* Sound Level Test

Environment: Refer to ISO 7779; Maximum HDD loaded; Bystander Position; Average data from 1 meter in front of operating NAS.

Product images are for illustrative purposes only and may differ from the actual product. Due to differences in monitors, colors of products may also appear different to those shown on the site.

Designs and specifications are subject to change without notice.