



QVP-41A	
OS	QVR Pro OS (QVP)
CPU	Intel® Pentium G5400T 2-core 3.1 GHz Processor
CPU Architecture	64-bit x86
Graphic Processors	Intel® UHD Graphics 610
System Memory	8 GB SODIMM DDR4 (2 x 4 GB)
Maximum Memory	32 GB (2 x 16 GB)
Memory Slot	2 x SO-DIMM DDR4
Flash Memory	5GB (Dual boot OS protection)
Max Live Cameras (Local Display)	24ch @ All 720p,H.264, 30FPS 12ch @ All 1080p,H.264, 30FPS
Max Playback Cameras (Local Display)	12
Max Concurrent Connection (Client)	8 (4 live cameras / per remote client) *The number of client concurrent connection varies by live cameras
Embedded Channel	8
Max Channel	24
Max Throughput	264 Mbps
Drive Bay	4 x 3.5-inch SATA 6Gb/s, 3Gb/s
Drive Compatibility	3.5-inch bays:3.5-inch SATA hard disk drives2.5-inch SATA hard disk drives2.5-inch SATA solid state drives
Hot-swappable	Yes
M.2 SSD Slot	2 x M.2 2280 PCIe Gen3 x2 slots
Gigabit Ethernet Port (RJ45)	2

PCIe Slot	2 Slot 1: PCIe Gen 3 x16 (CPU) Slot 2: PCIe Gen 3 x4 (PCH)
USB 3.2 Gen 1 port	1
USB 3.2 Gen 2 (10Gbps) Port	2 x Type-C USB 3.2 Gen2 5V/3A 10Gbps 2 x Type-A USB 3.2 Gen2 5V/1A 10Gbps
HDMI Output	1, HDMI 2.0 (up to 3840 x 2160 @ 60Hz)
Audio Input	1 x 3.5mm microphone input jacks
Audio Output	1 x built-in speaker, 1 x 3.5mm line out jack (for amplifiers or speakers)
Form Factor	Tower
LED Indicators	HDD 1-4, Status, LAN, USB port, M.2 port
LCD Display/ Button	Yes
Buttons	Power, Reset, USB Copy
Dimensions (HxWxD)	188.2 × 199.3 × 279.6 mm
Weight (Net)	5.4 kg
Weight (Gross)	7.01 kg
Operating temperature	0 - 40 °C (32°F - 104°F)
Relative Humidity	5-95% RH non-condensing, wet bulb: 27°C (80.6°F)
Power Supply Unit	250W, 100-240V
Power Consumption: HDD Sleep Mode	24.14 W
Power Consumption: Operating Mode, Typical	37.32 W
Fan	System fan: 1 x 120mm, 12VDC CPU fan: 2 x 60mm blower fan
	CPO Ian. 2 x bomin blower Ian
Sound Level	21.2 db(A)
Sound Level System Warning	
	21.2 db(A)
System Warning	21.2 db(A) Voice prompts or Buzzer
System Warning Tray Locker File System: Internal Hard	21.2 db(A) Voice prompts or Buzzer Yes
System Warning Tray Locker File System: Internal Hard Drive	21.2 db(A) Voice prompts or Buzzer Yes EXT4

RAID 10+ hot spare	Yes
RAID 10	Yes
RAID 6	Yes
RAID 5+ Spare	Yes
RAID 5	Yes
RAID 1	Yes
JBOD	Yes
Single Disk	Yes
Wake on LAN (WOL)	Yes
Schedule Power On/Off (15 settings)	Yes
Telnet & SSH logins (Admin only)	Yes
Syslog Server & Client	Yes
Language	English, German, French, Italian, Spanish, Polish, Swedish, Danish, Norwegian, Finnish, Russian, Japanese, Korean, Dutch, Czech, Traditional Chinese, Simplified Chinese, Turkish, Hungarian, Romanian, Thai, Portuguese/Brazil, Greek

Note: Use only QNAP memory modules to maintain system performance and stability. For NAS devices with more than one memory slot, use QNAP modules with identical specifications.

Warning: Using unsupported modules may degrade performance, cause errors, or prevent the operating system from starting.

* Sound Level Test

Environment: Refer to ISO 7779; Maximum HDD loaded; Bystander Position; Average data from 1 meter in front of operating NAS. Product images are for illustrative purposes only and may differ from the actual product. Due to differences in monitors, colors of products may also appear different to those shown on the site.

Designs and specifications are subject to change without notice.