



TS-h1277AXU-RP-R7-32G					
CPU	AMD Ryzen™ 7 7000 series 8-core/16-thread processor, burst up to 5.3 GHz				
	AMD Radeon Graphics				
CPU Architecture	64-bit x86				
Floating Point Unit	Yes				
Encryption Engine	Yes (AES-NI)				
Hardware-accelerated Transcoding	Yes				
System Memory	32 GB UDIMM DDR5 (1x 32 GB)				
Maximum Memory	128 GB (4 x 32 GB)				
Memory Slot	4 x UDIMM DDR5 Support optional ECC memory				
Flash Memory	5GB (Dual boot OS protection)				
Drive Bay	12 x 3.5-inch SATA 6Gb/s, 3Gb/s				
Drive Compatibility	3.5-inch SATA hard disk drives 2.5-inch SATA solid state drives				
Hot-swappable	Yes				
M.2 Slot	2 x M.2 2280 PCIe Gen 5 x2 slots				
	Compatible with NVMe SSD PCIe Gen 3 and above. Please refer to <a href="https://www.qnap.com/compatibility/">https://www.qnap.com/compatibility/</a> for compatibility.				
SSD Cache Acceleration Support	Yes				
GPU pass-through	Yes				
2.5 Gigabit Ethernet Port (2.5G/1G/100M)	2 (2.5G/1G/100M/10M)				
10 Gigabit Ethernet Port	2 x 10GBASE-T (10G/5G/2.5G/1G/100M)				

Wake on LAN (WOL)	Yes			
Jumbo Frame	Yes			
PCIe Slot	3 Slot 1: Gen 4 x 4 Slot 2: Gen 4 x 8 or Gen 4 x 4* Slot 3: Gen 4 x 4			
	*Slot 2 provides the width of PCIe Gen4 x8 when Slot 1 is not in use, and provides the width of PCIe Gen4 x4 when Slot 1 is in use.			
USB 3.2 Gen 2 (10Gbps) Port	2 x Type-A USB 3.2 Gen 2 10Gbps			
Form Factor	2U Rackmount			
LED Indicators	Power Status, HDD 1-12, M.2 SSD 1-2, Status, LAN, storage expansion port status			
Buttons	Power, Reset			
Dimensions (HxWxD)	88.6 × 432 × 511.2 mm			
	Excludes ear hook and the protruding part of the Power Supply Unit.			
Weight (Net)	13 kg			
Weight (Gross)	19 kg			
Operating Temperature	0 - 40 °C (32°F - 104°F)			
Storage Temperature	-20 - 70°C (-4°F - 158°F)			
Relative Humidity	5-95% RH non-condensing, wet bulb: 27°C (80.6°F)			
Power Supply Unit	550W(x2), 100-240V			
Fan	System fan: 3 x 60mm, 12VDC			
System Warning	Buzzer			
Standard Warranty	5			
Max. Number of Concurrent Connections (CIFS) - with Max. Memory	5000			

Note: Use only QNAP memory modules to maintain system performance and stability. For NAS devices with more than one memory slot, use QNAP modules with identical specifications.

Warning: Using unsupported modules may degrade performance, cause errors, or prevent the operating system from starting. QNAP reserves the right to replace partial parts or accessories if the original is no longer available from its manufacturer/supplier. Any replacement would be fully tested and verified to meet strict compatibility and stability guidelines and will deliver identical performance to the original.

The terms HDMI, HDMI High-Definition Multimedia Interface, HDMI trade dress and the HDMI Logos are trademarks or registered trademarks of HDMI Licensing Administrator, Inc.

Product images are for illustrative purposes only and may differ from the actual product. Due to differences in monitors, colors of products may also appear different to those shown on the site.

Designs and specifications are subject to change without notice.